

Pelican lifeline hook - Length: 170 mm - M14*200


Part #12837



Description

An easy and effective way to close the lifelines gates
The excentric shape and the length of the arm on the pelican hook allow the wires to be tensioned easily
Tension: 28 mm

Technical information

| | |
|---|----------------------------------|
| Materials | HR 17.4 PH stainless steel grade |
| Length (mm) | 170 |
|  Working load (kg) | 3200 |
| Breaking load (kg) | 6500 |
| Weight (g) | 534 |
| A (mm) | 20 |
| B (mm) | 18 |
| C (mm) | M14 x 200 |

Caption



Working load (WL) : for nautical applications



Working Load Limit (WLL): for industrial applications only.
The safety factor is 5 times the breaking load.
 $WLL = \text{Breaking load} / 5$

Wichard s'efforce d'assurer au mieux de ses possibilités, l'exactitude et la mise à jour des informations diffusées sur ce document, dont il se réserve le droit de corriger à tout moment et sans préavis le contenu, ainsi que de faire évoluer ses produits.

Dans le cas d'une application industrielle, merci de prendre contact avec notre service commercial et technique afin de valider l'utilisation de ces produits. La demande de certificats peut être faite directement auprès du service commercial.

Photos non contractuelles.