

# Data Sheet

## PS 22 K Discs with paper backing, self-fastening for Wood, Metals



### Applications

Wood	●
Metals	●
Stainless steel	○
Paint	○
Varnish	○
Filler	○
Plastic	○

### Properties

Bonding agent	Resin
Grain	Aluminium oxide
Coating	Semi-open
Backing	E-paper

### Cut down on your sanding time – the abrasive disc PS 22 K

The **abrasive disc PS 22 K** helps the user save time when treating surfaces. The abrasive truly shines when used on

- **wood** and
- **metal**.

Its self-fastening support allows for a quick tool change, reducing retooling times significantly. The disc is fitted and ready for use in seconds, while detaching it from the backing pad is just as quick and easy. These are advantages that neither hobby craftsmen nor professional users want to live without.

### The abrasive disc PS 22 K – outstanding results, long service life

The **PS 22 K** is a **hook and loop abrasive disc** designed to deliver a superior level of dependability and durability. Fixed in place with a synthetic resin, a high-quality velour fabric is bonded to the **paper backing (E-paper)**. Even if subjected to high contact pressure, the velour fabric will stay securely connected to the backing pad. Safe, confident and reliable work is possible even at high process temperatures. Professionals who do not want to compromise on their work therefore rely on the sanding discs from the Klingspor range. This is why professionals who need to work without any compromises put their trust in the abrasive disc included in the product portfolio offered by Klingspor.

### Universal suitability

An ideal match with handheld machines, the **abrasive disc** delivers a uniform scratch pattern every time. Premature clogging during woodwork is prevented by the semi-open coating. When used for processing metal, the product excels thanks to the exceptional grit adhesion, which is brought about by the synthetic resin bond of the grain to the backing. To ensure their **abrasive disc PS 22 K** is an excellent option for a wide variety of sanding tasks, Klingspor makes this product available in a host of grit sizes and hole patterns. The hole patterns have been paired perfectly with the extraction holes found in all standard backing pads. With the HST 555, Klingspor offers their own backing pad as the perfect companion product to the self-fastening discs **PS 22 K**. This backing pad brings out the maximum performance these abrasive tasks are capable of delivering. Topping off the product's unique properties is its suitability for universal use on all types of random orbital sanders.

Diameter in mm	Grit	Hole pattern	Cat.number	Availability
----------------	------	--------------	------------	--------------

150	220	hole pattern GLS3	100157
125	400	hole pattern GLS5	104778
115	400	no hole	111470
150	400	hole pattern GLS3	128356
150	400	no hole	129092
150	400	hole pattern GLS1	129389
125	400	no hole	130114
150	40	no hole	20207
125	40	no hole	2294
125	60	no hole	2295
125	100	no hole	2296
150	24	no hole	2474
180	40	no hole	2476
180	60	no hole	2477
125	40	hole pattern GLS27	260795
125	60	hole pattern GLS27	260796
125	80	hole pattern GLS27	260797
125	100	hole pattern GLS27	260798
125	120	hole pattern GLS27	260799
125	150	hole pattern GLS27	260800
125	180	hole pattern GLS27	260801
125	240	hole pattern GLS27	260802
180	24	no hole	2782
180	100	no hole	2783
115	40	no hole	2785
115	60	no hole	2786
115	100	no hole	2787
115	180	no hole	2788
150	80	hole pattern GLS51	305559
150	120	hole pattern GLS51	305560
150	100	hole pattern GLS51	306507
150	150	hole pattern GLS51	306508
150	180	hole pattern GLS51	306509
150	40	hole pattern GLS51	306611
150	60	hole pattern GLS51	306612
150	240	hole pattern GLS51	309471
150	240	hole pattern GLS74	340761
150	80	hole pattern GLS74	340766
150	120	hole pattern GLS74	342159
150	60	hole pattern GLS74	342418

150	40	hole pattern GLS74	342419
150	180	hole pattern GLS74	342421
150	150	hole pattern GLS74	342422
150	100	hole pattern GLS74	342423
150	180	no hole	4022
125	180	no hole	62107
150	24	hole pattern GLS1	6516
150	40	hole pattern GLS1	6520
150	60	hole pattern GLS1	6523
150	80	hole pattern GLS1	6524
150	100	hole pattern GLS1	6525
150	120	hole pattern GLS1	6526
150	180	hole pattern GLS1	6611
150	60	no hole	6649
150	100	no hole	6697
115	24	no hole	6754
115	80	no hole	6756
115	120	no hole	6757
125	80	no hole	6774
125	120	no hole	6775
180	80	no hole	6914
180	120	no hole	6915
150	80	no hole	6936
150	120	no hole	6937
150	150	no hole	71140
150	180	hole pattern GLS2	72624
150	120	hole pattern GLS2	72628
150	80	hole pattern GLS2	72632
150	60	hole pattern GLS2	72633
125	24	no hole	7300
150	100	hole pattern GLS2	73490
150	40	hole pattern GLS2	74088
200	80	no hole	77656
200	100	no hole	77658
200	40	no hole	77659
200	60	no hole	77660
200	120	no hole	77661
125	150	no hole	78163
150	150	hole pattern GLS2	79862
115	150	no hole	80046

150	150	hole pattern GLS1	80722
115	40	hole pattern GLS4	82938
115	60	hole pattern GLS4	82940
115	80	hole pattern GLS4	82941
115	100	hole pattern GLS4	82942
115	120	hole pattern GLS4	82944
115	180	hole pattern GLS4	82946
150	60	hole pattern GLS3	86634
150	80	hole pattern GLS3	86635
150	120	hole pattern GLS3	86636
150	150	hole pattern GLS3	86637
115	240	hole pattern GLS4	87424
150	180	hole pattern GLS3	87528
115	220	no hole	88330
115	240	no hole	88333
150	40	hole pattern GLS3	89181
150	320	hole pattern GLS1	89450
150	240	hole pattern GLS1	89451
125	24	hole pattern GLS5	89485
125	40	hole pattern GLS5	89486
125	60	hole pattern GLS5	89488
125	80	hole pattern GLS5	89489
125	100	hole pattern GLS5	89491
125	120	hole pattern GLS5	89493
125	150	hole pattern GLS5	89494
125	180	hole pattern GLS5	89495
125	320	hole pattern GLS5	89496
125	220	hole pattern GLS5	90758
150	240	no hole	91605
150	320	no hole	91721
150	240	hole pattern GLS2	91814
125	240	no hole	91922
125	240	hole pattern GLS5	92753
125	320	no hole	93284
150	24	hole pattern GLS3	93321
150	220	no hole	93324
115	320	no hole	95561
150	100	hole pattern GLS3	97072
125	220	no hole	97176
150	240	hole pattern GLS3	97778

150

320

hole pattern GLS3

97779

150

220

hole pattern GLS1

98990