



## Self-locking bow shackle - Dia 10 mm

Part #1245



### Description

Self-locking bow shackle forged in grade 316L stainless steel  
The pin is locked into one of the indentations  
No risks of loose due to vibrations  
Outstanding working and breaking loads  
WLL: only for industrial applications (lifting i.e...)  
CE marking and batch number

### Applications

To be used when ample room is required  
Possibility to attach several lines or cables

## Technical information

|                                                                                     | Materials          | 316 stainless steel grade |
|-------------------------------------------------------------------------------------|--------------------|---------------------------|
|  | Working load (kg)  | 1520                      |
|  | WLL (kg)           | 860                       |
|                                                                                     | Breaking load (kg) | 4300                      |
|                                                                                     | Weight (g)         | 137                       |
|                                                                                     | A (mm)             | 47                        |
|                                                                                     | B (mm)             | 20                        |
|                                                                                     | C (mm)             | 10                        |
|                                                                                     | D (mm)             | 20                        |
|                                                                                     | D diameter (mm)    | 10                        |
|                                                                                     | E (mm)             | 9                         |
|                                                                                     | M (mm)             | 52                        |

### Caption



Working load (WL) : for nautical applications



Working Load Limit (WLL): for industrial applications only.  
The safety factor is 5 times the breaking load.  
 $WLL = \text{Breaking load} / 5$

Wichard s'efforce d'assurer au mieux de ses possibilités, l'exactitude et la mise à jour des informations diffusées sur ce document, dont il se réserve le droit de corriger à tout moment et sans préavis le contenu, ainsi que de faire évoluer ses produits.

Dans le cas d'une application industrielle, merci de prendre contact avec notre service commercial et technique afin de valider l'utilisation de ces produits. La demande de certificats peut être faite directement auprès du service commercial.

Photos non contractuelles.