


Captive pin D shackle - Dia 8 mm

Part #1404



Description

Captive pin "D" shackle forged in grade 316L stainless steel
The pin is connected to the body at all times even when opened
The pin is locked into one of the indentations
No risks of loose due to vibrations
Outstanding working and breaking loads
le ma

Applications

Standard applications of shackle
Attachment applications: blocks, head ...

Technical information

	Materials	316 stainless steel grade
	Working load (kg)	1000
	WLL (kg)	720
	Breaking load (kg)	3600
	Weight (g)	61
	A (mm)	26
	B (mm)	16
	C (mm)	9
	D (mm)	18
	D diameter (mm)	8
	E (mm)	8
	F (mm)	47
	G (mm)	42

Caption



Working load (WL) : for nautical applications



Working Load Limit (WLL): for industrial applications only.
The safety factor is 5 times the breaking load.
 $WLL = \text{Breaking load} / 5$

Wichard s'efforce d'assurer au mieux de ses possibilités, l'exactitude et la mise à jour des informations diffusées sur ce document, dont il se réserve le droit de corriger à tout moment et sans préavis le contenu, ainsi que de faire évoluer ses produits.

Dans le cas d'une application industrielle, merci de prendre contact avec notre service commercial et technique afin de valider l'utilisation de ces produits. La demande de certificats peut être faite directement auprès du service commercial.

Photos non contractuelles.