


# Watertight U-bolt - Dia I2 mm - Length: I30 mm - White

Part #65462





# Description

Fully dropforged product with high quality stainless steel Outstanding working and breaking loads

Complete watertightness thanks to the resistant rubber collar (white colour)

Easy installation (no need to use a waterproof sealant) For any kind of fastening applications (shrouds, lifeline, blocks...)

Delivered with bolts and counterplate

## **Applications**

Various fastening applications: shrouds, lifelines, blocks...

#### Technical information

lack

Materials	316L stainless steel grade
Colour	White
Length (mm)	130
Working load (kg)	6400
Breaking load (kg)	10000
Weight (g)	375
A (mm)	44
B (mm)	27
C (mm)	70
D diameter (mm)	12

# Caption



Working load (WL): for nautical applications



Working Load Limit (WLL): for industrial applications only.

The safety factor is 5 times the breaking load.  $WLL = Breaking\ load\ /\ 5$ 

Wichard s'efforce d'assurer au mieux de ses possibilités, l'exactitude et la mise à jour des informations diffusées sur ce document, dont il se réserve le droit de corriger à tout moment et sans préavis le contenu, ainsi que de faire évoluer ses produits.

Dans le cas d'une application industrielle, merci de prendre contact avec notre service commercial et technique afin de valider l'utilisation de ces produits. La demande de certificats peut être faite directement auprès du service commercial.

Photos non contractuelles