


Double folding pad eye - Dia IO mm

Part #6566




Description

Fully dropforged product with outstanding working and breaking loads regardless the angle of the load
Perfect solution attachment (stay, blocks, jib tack point)
Possibility to attach several stays
Modern and optimized design to suit aesthetics of modern boats
They can be fold down to minimize the risk of injuries
The silicon pad eliminates noise and unpleasant vibrations

Applications

For any fastening/attachment application
Allows to attach several shrouds

Technical information

Materials	316L stainless steel grade
 Working load (kg)	4560
Breaking load (kg)	9000
Weight (g)	494
A (mm)	75
B (mm)	45
C (mm)	23
d diameter (mm)	10.5
D diameter (mm)	10
E (mm)	104
F (mm)	78

Caption



Working load (WL) : for nautical applications



Working Load Limit (WLL): for industrial applications only.
The safety factor is 5 times the breaking load.
WLL = Breaking load / 5

Wichard s'efforce d'assurer au mieux de ses possibilités, l'exactitude et la mise à jour des informations diffusées sur ce document, dont il se réserve le droit de corriger à tout moment et sans préavis le contenu, ainsi que de faire évoluer ses produits.

Dans le cas d'une application industrielle, merci de prendre contact avec notre service commercial et technique afin de valider l'utilisation de ces produits. La demande de certificats peut être faite directement auprès du service commercial.

Photos non contractuelles.