

# BN 6205

## TECHNICAL TAPE

Semicreped paper tape with natural rubber and resins adhesive, used for masking in building and painting industry.

### MAIN APPLICATIONS AND ADVICES FOR THE CORRECT TAPE USE

- Used for masking in building and painting industry. For applications at 40-60°C.

### TECHNICAL DATA

BACKING	Impregnated semi-creped paper 95 $\mu\text{m}$
BACKING COLOR	Natural paper
ADHESIVE	Natural rubber and resins
TOTAL THICKNESS	100 $\mu\text{m}$ (AFERA 4006-ED.9/79)
ADHESION TO STEEL	> 120 cN/cm (AFERA 4001-ED.10/87)

\*Non-representative results can occur if test guidelines are not followed.

### WARRANTY

The material should be protected from extreme temperatures and direct sunlight. Once removed from its original packaging, the tape should be protected from dust and other impurities. Keep the rolls in horizontal position. The technical information and data, recommendations, and other statements provided in this document are based on Boston tapes tests or experience. It will be up to the user matching the product with the working process or surface. Boston tapes will not be, at any rate, held responsible for not proper use. Warranty is limited to replacement of products that Boston tapes proves to be defective and keeps out any other damages.

[www.bostontapes.com](http://www.bostontapes.com) - [info@bostontapes.com](mailto:info@bostontapes.com)

BOSTON tapes S.p.A.

Company under direction and coordination activity of Novacel S.A.

Registered Office and Plant : Strada Provinciale Cellole - Piedimonte - 81037 Sessa Aurunca (CE)-ITALY. Phone: 0823 680211 Fax: 0823 703889

Registration C.C.I.A. (Ce) n° 132712 Reg. Trib. 11772/91

