


Key pin shackle - Dia 5 mm

Part #1432




Description

Key pin shackle forged in grade 316L stainless steel
Opening and closing is done simply by rotating the pin half a turn
No risk to lose the pin as it remains attached
Outstanding working and breaking loads

Applications

Perfect product for halyards or applications requiring to open /close the shackle often

Technical information

| | |
|---|---------------------------|
| Materials | 316 stainless steel grade |
|  Working load (kg) | 400 |
| Breaking load (kg) | 1000 |
| Weight (g) | 31 |
| A (mm) | 37 |
| B (mm) | 13 |
| C (mm) | 5 |
| D (mm) | 11 |
| D diameter (mm) | 5 |
| E (mm) | 4 |
| F (mm) | 49 |
| G (mm) | 31 |

Caption



Working load (WL) : for nautical applications



Working Load Limit (WLL): for industrial applications only.
The safety factor is 5 times the breaking load.
 $WLL = \text{Breaking load} / 5$

Wichard s'efforce d'assurer au mieux de ses possibilités, l'exactitude et la mise à jour des informations diffusées sur ce document, dont il se réserve le droit de corriger à tout moment et sans préavis le contenu, ainsi que de faire évoluer ses produits.

Dans le cas d'une application industrielle, merci de prendre contact avec notre service commercial et technique afin de valider l'utilisation de ces produits. La demande de certificats peut être faite directement auprès du service commercial.

Photos non contractuelles.