## **SAFETY DATA SHEET**

### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation

5-56 PRO

of the mixture

**Synonyms** None.

BDS001899 **Product code** 29-July-2020 Issue date

Version number

1.2. Relevant identified uses of the substance or mixture and uses advised against

**Identified uses** Lubricants None known. Uses advised against 1.3. Details of the supplier of the safety data sheet

CRC Industries Europe byba Company name

**Address** Touwslagerstraat 1

> 9240 Zele Belgium

**Telephone** +32(0)52/45.60.11 Fax +32(0)52/45.00.34 E-mail hse@crcind.com Website www.crcind.com

1.4. Emergency telephone

number

Tel.: +32(0)52/45.60.11 (office hours)

#### **SECTION 2: Hazards identification**

### 2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

### Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards

H223 - Flammable aerosol. Aerosols Category 2

H229 - Pressurized container: May

burst if heated.

Aerosol CONTENTS UNDER PRESSURE. **Hazard summary** 

Pressurised container may explode when exposed to heat or flame. Not classified for health hazards. However, occupational exposure to the mixture or substance(s) may cause adverse

health effects.

#### 2.2. Label elements

#### Label according to Regulation (EC) No. 1272/2008 as amended

**Hazard pictograms** 

Signal word Warning

**Hazard statements** 

Flammable aerosol. H223

Pressurized container: May burst if heated. H229

**Precautionary statements** 

Prevention

Keep out of reach of children. P102

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P210

Do not spray on an open flame or other ignition source. P211

Do not pierce or burn, even after use. P251

Response Not available.

Material name: 5-56 PRO - Manufacturers SDS UK Storage

P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.

**Disposal** Not available.

Supplemental label information EUH066 - Repeated exposure may cause skin dryness or cracking.

2.3. Other hazards None of the ingredients of this mixture does meet vPvB / PBT criteria of Regulation (EC) No

1907/2006, Annex XIII.

### **SECTION 3: Composition/information on ingredients**

#### 3.2. Mixtures

#### **General information**

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Hydrocarbons, C11-C14, n-alkanes,	50 - 75	EC926-141-6	01-2119456620-43	-	
isoalkanes, cyclics, < 2% aromatics		-			
Classification:	Asp. Tox.	1;H304			
Carbon dioxide	1 - 5	124-38-9	Exempt	-	#
		204-696-9	·		
Classification:	Press. Ga	s;H280			
Sulphonic acids, petroleum, sodium	1 - 5	68608-26-4	01-2119527859-22	-	
salts		271-781-5			
Classification:	Eye Irrit. 2	;H319			

### List of abbreviations and symbols that may be used above

#: This substance has been assigned Union workplace exposure limit(s).

M: M-factor

PBT: persistent, bioaccumulative and toxic substance. vPvB: very persistent and very bioaccumulative substance.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments The full text for all H-statements is displayed in section 16.

### **SECTION 4: First aid measures**

**General information** Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves.

4.1. Description of first aid measures

InhalationIf symptoms develop move victim to fresh air. Get medical attention if symptoms persist.Skin contactWash off with soap and water. Get medical attention if irritation develops and persists.

**Eye contact**Rinse with water. Get medical attention if irritation develops and persists. **Ingestion**In the unlikely event of swallowing contact a physician or poison control centre.

4.2. Most important symptoms and effects, both acute and

delayed

Exposure may cause temporary irritation, redness, or discomfort.

4.3. Indication of any Trea immediate medical attention

immediate medical attention and special treatment needed Treat symptomatically.

#### **SECTION 5: Firefighting measures**

General fire hazards Flammable aerosol.

5.1. Extinguishing media

Suitable extinguishing

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

media

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Contents under pressure. Pressurised container may explode when exposed to heat or flame.

During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Special fire fighting procedures

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapour pressure build up. For massive fire in cargo area, use unmanned hose

holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

**Specific methods**Use standard firefighting procedures and consider the hazards of other involved materials. In the

event of fire and/or explosion do not breathe fumes.

#### **SECTION 6: Accidental release measures**

#### 6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

For emergency responders

Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the

6.2. Environmental precautions

Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to

remove residual contamination.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

### **SECTION 7: Handling and storage**

7.1. Precautions for safe handling

Pressurised container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities

Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS).

7.3. Specific end use(s) Not available.

### **SECTION 8: Exposure controls/personal protection**

#### 8.1. Control parameters

Occupational exposure limits

**UK. EH40 Workplace Exposure Limits (WELs)** 

Components	Туре	Value	
Carbon dioxide (CAS 124-38-9)	STEL	27400 mg/m3	
		15000 ppm	
	TWA	9150 mg/m3	
		5000 ppm	

EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU							
Components	Type	Value					
Carbon dioxide (CAS 124-38-9)	TWA	9000 mg/m3					

No biological exposure limits noted for the ingredient(s).

5000 ppm

**Recommended monitoring** procedures

**Biological limit values** 

Follow standard monitoring procedures.

Derived no effect levels (DNELs)

Workers

Components Value Assessment factor Notes

Petrolatum; Petrolatum; [A complex combination of hydrocarbons obtained as a semi-solid from dewaxing paraffinic residual oil. It consists predominantly of saturated crystalline and liquid hydrocarbons having carbon numbers predominantly greater than C25. (CAS 8009-03-8)

Long-term, Systemic, Dermal 5.8 mg/kg Long-term, Systemic, Inhalation 2.7 mg/m3

Predicted no effect

Not available.

concentrations (PNECs)

8.2. Exposure controls

Appropriate engineering

controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been

established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

**General information** Use personal protective equipment as required. Personal protection equipment should be chosen

according to the CEN standards and in discussion with the supplier of the personal protective

equipment.

Eye/face protection

Use eye protection conforming to EN 166.

Skin protection

When handling the product wear chemical-resistant gloves (standard EN 374). The breakthrough - Hand protection

> time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. Full contact: Glove material: nitrile. Use gloves with breakthrough time of 480 minutes. Minimum glove thickness 0.38 mm.

- Other Not available.

In case of insufficient ventilation, wear suitable respiratory equipment. Chemical respirator with Respiratory protection

organic vapour cartridge.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

When using do not smoke. Always observe good personal hygiene measures, such as washing Hygiene measures

after handling the material and before eating, drinking, and/or smoking. Routinely wash work

clothing and protective equipment to remove contaminants.

**Environmental exposure** 

controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. Fume scrubbers, filters or

engineering modifications to the process equipment may be necessary to reduce emissions to

### **SECTION 9: Physical and chemical properties**

### 9.1. Information on basic physical and chemical properties

**Appearance** 

**Physical state** Liquid. Aerosol Form Colour Amber Odour Salicylate. Odour threshold Not available. Not applicable.

Melting point/freezing point -56.6 °C (-69.9 °F) estimated

Initial boiling point and boiling

range

Not available.

78.0 °C (172.4 °F) Closed cup

**Evaporation rate** Not available. Flammability (solid, gas) Not available. Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

Flash point

Flammability limit - upper

(%)

Not available.

Not available. Vapour pressure Vapour density Not available. 0.82 g/cm3 Relative density 20 °C (68 °F) Relative density temperature

Solubility(ies)

Emulsifies with water Solubility (water)

Partition coefficient

Not available.

(n-octanol/water)

> 200 °C (> 392 °F) Auto-ignition temperature **Decomposition temperature** Not available. Not available. **Viscosity Explosive properties** Not explosive.

Not oxidising Oxidising properties

9.2. Other information

Aerosol spray enclosed space

**Deflagration density**  $> 400 \text{ s/m}^3$ Aerosol spray ignition 60 cm

distance

Lubricant Chemical family 560 g/l VOC

### **SECTION 10: Stability and reactivity**

10.1. Reactivity The product is stable and non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability Material is stable under normal conditions.

10.3. Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Avoid high temperatures. 10.4. Conditions to avoid 10.5. Incompatible materials Strong oxidising agents.

Carbon oxides. 10.6. Hazardous

decomposition products

### **SECTION 11: Toxicological information**

**General information** Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact Based on available data, the classification criteria are not met. Eye contact Based on available data, the classification criteria are not met.

May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of Ingestion

occupational exposure.

**Symptoms** Exposure may cause temporary irritation, redness, or discomfort.

#### 11.1. Information on toxicological effects

**Acute toxicity** Based on available data, the classification criteria are not met. Skin corrosion/irritation Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Serious eye damage/eye

irritation

Respiratory sensitisation Based on available data, the classification criteria are not met. Skin sensitisation Based on available data, the classification criteria are not met. Germ cell mutagenicity Based on available data, the classification criteria are not met. Carcinogenicity Based on available data, the classification criteria are not met. Based on available data, the classification criteria are not met. Reproductive toxicity

Specific target organ toxicity -

single exposure

Based on available data, the classification criteria are not met.

Specific target organ toxicity -

repeated exposure

Based on available data, the classification criteria are not met.

Based on available data, the classification criteria are not met. Aspiration hazard

Mixture versus substance

information

Not available

Other information Not available.

### **SECTION 12: Ecological information**

12.1. Toxicity The product is not classified as environmentally hazardous. However, this does not exclude the

possibility that large or frequent spills can have a harmful or damaging effect on the environment.

12.2. Persistence and

12.4. Mobility in soil

degradability

No data is available on the degradability of any ingredients in the mixture.

12.3. Bioaccumulative potential

**Partition coefficient** 

Not available

n-octanol/water (log Kow)

**Bioconcentration factor (BCF)** Not available. No data available

Material name: 5-56 PRO - Manufacturers

BDS001899 Version #: 01 Issue date: 29-July-2020

12.5. Results of PBT and vPvB

This mixture does not meet vPvB / PBT criteria of Regulation (EC) No 1907/2006, Annex XIII.

assessment

The product contains volatile organic compounds which have a photochemical ozone creation 12.6. Other adverse effects

potential.

### **SECTION 13: Disposal considerations**

13.1. Waste treatment methods

Residual waste Dispose of in accordance with local regulations. Empty containers or liners may retain some

product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Since emptied containers may retain product residue, follow label warnings even after container is Contaminated packaging

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal. Do not re-use empty containers.

The Waste code should be assigned in discussion between the user, the producer and the waste EU waste code

disposal company.

Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents Disposal methods/information

under pressure. Do not puncture, incinerate or crush. Dispose of contents/container in accordance

with local/regional/national/international regulations.

Special precautions Dispose in accordance with all applicable regulations.

### **SECTION 14: Transport information**

#### **ADR**

14.1. UN number UN1950

14.2. UN proper shipping

**AEROSOLS** 

name

14.3. Transport hazard class(es)

Class 2.1 Subsidiary risk

Hazard No. (ADR) Not available.

**Tunnel restriction code** (D) ADR/RID - Classification 5F

code:

14.4. Packing group Not applicable

14.5. Environmental hazards No.

14.6. Special precautions Read safety instructions, SDS and emergency procedures before handling.

for user

**IATA** 

14.1. UN number UN1950 **AEROSOLS** 14.2. UN proper shipping

name

14.3. Transport hazard class(es)

Subsidiary risk

14.4. Packing group Not applicable

14.5. Environmental hazards No

Read safety instructions, SDS and emergency procedures before handling. 14.6. Special precautions

for user

**IMDG** 

14.1. UN number UN1950 **AEROSOLS** 14.2. UN proper shipping

14.3. Transport hazard class(es) Class 2.1

Subsidiary risk

14.4. Packing group Not applicable

14.5. Environmental hazards

Marine pollutant **EmS** 

14.6. Special precautions

Read safety instructions, SDS and emergency procedures before handling.

for user

Not established. 14.7. Transport in bulk

according to Annex II of MARPOL 73/78 and the IBC

Code

BDS001899 Version #: 01 Issue date: 29-July-2020

#### ADR; IATA; IMDG



### **SECTION 15: Regulatory information**

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture EU regulations

Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended Not listed.

Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended

Not listed

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended

Not listed

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended Not listed.

Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended Not listed.

Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended Carbon dioxide (CAS 124-38-9)

Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA Not listed.

#### **Authorisations**

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended Not listed.

### Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended Not listed.

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

#### Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended Not listed.

### Other regulations

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.

#### **National regulations**

This safety data sheet conforms to the following laws, regulations and standards:

This safety data sheet conforms to the following laws, regulations and standards:

Act on the management of packaging and packaging waste of June 13, 2013

Regulation of the Minister of Health of June 11, 2012 on the categories of dangerous substances and dangerous preparations whose packaging should be fitted with child-resistant closures and a tactile warning of danger

REGULATION OF THE MINISTER OF HEALTH of February 2, 2011 on tests and measurements of factors harmful to health in working environments

Regulation of Ministry of Labor and Social Policy of June 6, 2014. On the matter of maximum permissible concentrations and intensities of harmful factors in the work environment (Journal of Laws 2014, item. 817)

Chemical Safety at Workplace Ordinance Joint Decree No. 25/2000 (Annex 2): Permissible limit values of biological exposure (effect) indices Decree No. 25/2000. (IX. 30.) EüM-SzCsM of the Minister of Health and the Minister of Social and Family Affairs on chemical safety at work Act No. 93 of 1993 on Labour Safety (1993.évi XCIII.), as amended

Government Decree No. 220 of 2004 (VII. 21.) providing rules on the protection of surface waters quality

Government Decree No. 98/2001 (VI. 15.), on the conditions of the activities related to hazardous waste, and Ministry of Environmental Affairs Decree No. 16/2001 (VII. 18.), on the register of waste s Public Act No. XXV of 2000 on Chemical Safety, and Application Decree No. 44/2000. (XII.27.) EüM [of the Ministry of Health]

Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended

# 15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

#### **SECTION 16: Other information**

#### List of abbreviations

ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road.

ATE: Acute Toxicity Estimate according to REGULATION (EC) No 1272/2008 (CLP).

Ceiling: Short Term Exposure Limit Ceiling value.

CLP: Classification, Labeling and Packaging REGULATION (EC) No 1272/2008 on classification,

labeling and packaging of substances and mixtures.

GWP: Global Warming Potential.

IATA: International Air Transport Association.

MAK: Threshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG).

REACH: Registration, Evaluation and Authorization of Chemicals (REGULATION (EC) No 1907/2006 concerning Registration, Evaluation Authorization and Restriction of Chemicals). RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement

International concernant le transport de marchandises dangereuses par chemin de fer).

TLV: Threshold Limit Value.

TWA: Time Weighted Average.

VOC: Volatile organic compounds.

STEL: Short-term Exposure Limit.

Use category (UC62) (KT)

02: Adhesives, binding agents

07: Anti-static agents

09: Cleaning/washing agents

14: Corrosion inhibitors

28: Fuel additives

30: Hydraulic fluids and additives

35: Lubricants and additives

48: Solvents

54: Welding and soldering agents

55: Others

56: Cutting fluids

Not available.

59: Paints, lacquers and varnishes

methods and test data, if available.

### References

Information on evaluation method leading to the classification of mixture

Full text of any H-statements not written out in full under Sections 2 to 15

The classification for health and environmental hazards is derived by a combination of calculation

H280 Contains gas under pressure; may explode if heated.

H304 May be fatal if swallowed and enters airways.

H319 Causes serious eye irritation.

**Revision information** 

None.

**Training information** Follow training instructions when handling this material.

### Disclaimer

CRC Industries Europe byba cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.