

## MOTOR FLUSH

### 1. General description

Removes sludge, gum, rust and varnish from interior engine parts (gasoline & diesel). Use prior to oil change.

### 2. Features

- High performance dispersant.
- Provides excellent control of engine deposits under stop-go conditions.
- Ensures, the engine oil reaches, all places for good lubrication and cooling.
- Superior wear and bearing corrosion control, giving maximum engine protection.

### 3. Applications

- Suited for semi-synthetic mineral and synthetic motor oils.

### 4. Directions

- Add the complete can, undiluted. One can is sufficient for a passengers car.
- Run the engine for 10 minutes with the heater on.
- Stop engine.
- Exchange the oil according to the manufacturers instructions.
- **A safety data sheet (MSDS) according to EC Regulation N° 1907/2006 Art.31 and amendments is available for all CRC products.**

### 5. Typical product data (without propellant)

Appearance	Liquid.
Color	Colorless.
Odor	Characteristic odor.
Density	0.82 g/cm <sup>3</sup> (@ 20°C).
Flash Point	> 70 °C

### Remarks

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment, conditions of use and the unpredictable human factors involved, we recommend that our products are tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied. This Technical Data Sheet may already have been revised as a result of a change in legislation, availability of components or newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: [www.crcind.com](http://www.crcind.com) We recommend that you register on our website for this product, thus enabling you to automatically receive any future updates.

**Version**

CRC\_RED-MOTOR\_FLUSH-20181115



# Technical Data Sheet

---

## MOTOR FLUSH

---

**Date**

15/11/2018

