



## OIL DRIP STOP

### 1. General description

Stops motor oil leaks, reduces oil consumption and pollution. Compatible with all motor oil types.

### 2. Features

- Contains a viscosity improver.
- A synthetic seal swell additive.
- Works quickly.
- Eliminates in the need for expensive and time consuming engine overhauls.

### 3. Applications

- Suited for semi-synthetic mineral and synthetic motor oils.

### 4. Directions

- Add the complete can, undiluted. One can is sufficient for a passengers car.
- **A safety data sheet (MSDS) according to EC Regulation N° 1907/2006 Art.31 and amendments is available for all CRC products.**

### 5. Typical product data (without propellant)

Appearance	Liquid.
Color	Amber.
Odor	Characteristic odor.
Density	0.91 g/cm <sup>3</sup> (@ 20°C).
Flash Point	> 62 °C

### Remarks

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment, conditions of use and the unpredictable human factors involved, we recommend that our products are tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied. This Technical Data Sheet may already have been revised as a result of a change in legislation, availability of components or newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: [www.crcind.com](http://www.crcind.com) We recommend that you register on our website for this product, thus enabling you to automatically receive any future updates.

**Version** CRC\_RED-OIL\_DRIP\_STOP\_ADDITIVE\_II-20181115  
**Date** 15/11/2018

