

Cutting-off wheel

A 330 EXTRA



Properties

Bonding agent	Synthetic resin, fibre-reinforced
Type of grain	Aluminium oxide
Bond	■■■■■□□
Aggression	■■■■■□□
Service life	■■■■■□□

Product benefit

More stability during cutting due to two glass fibre reinforcement mesh - Good cutting speed with a long service life - Recommended for various materials and different profiles - Usable on chop saws in craft and industry

Application

Steel	●
Stainless steel	◐
Aluminium	◑
Castings	◒

Target group

- ▶ Plant engineering
- ▶ Apparatus and container manufacturing
- ▶ Locksmith's shop
- ▶ Steel construction
- ▶ Road building
- ▶ Construction above and below ground

Diameter x Width x Bore in mm	Form	Max. operating speed	Max. RPM	Packing unit/pcs.	Cat. number
305 x 2,5 x 25,4	— —	80 m/s	5100 rpm	10	360976
356 x 2,5 x 25,4	— —	80 m/s	4400 rpm	10	353326
406 x 3 x 25,4	— —	80 m/s	3800 rpm	10	353329

Klingspor Schleifsysteme GmbH und Co. KG

Hüttenstraße 36 - 35708 Haiger - Germany
 Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
 sales@klingspor.de - www.klingspor.de

