

## MAGIC OIL

### 1. General description

Long lasting lubricant for smooth lock operation.

### 2. Features

- Provides long lasting lubrication.
- Excellent water resistance.
- Resists salt water.
- Functional over a wide temperature range.
- Produces a very low coefficient of friction.
- Lubricates without leaving a sticky residue and prevents fingerprinting on shiny metals.
- Safe on all metal surfaces, does not stain.

### 3. Applications

- Locks.
- Fine mechanics.

### 4. Directions

- Shake well before use.
- Apply sparingly by pushing the special nozzle in the lock opening.
- Repeat if necessary.
- To remove residues or excess product, use one of the CRC cleaners.
- **A safety data sheet (MSDS) according to EC Regulation N° 1907/2006 Art.31 and amendments is available for all CRC products.**

### 5. Typical product data (without propellant)

Appearance	Solid.
Density	0.75 g/cm <sup>3</sup> (@ 20°C).
Flash Point	< 0 °C

### Remarks

All statements in this publication are based on service experience and/or laboratory testing. Because of the wide variety of equipment, conditions of use and the unpredictable human factors involved, we recommend that our products are tested on-the-job prior to use. All information is given in good faith but without warranty neither expressed nor implied. This Technical Data Sheet may already have been revised as a result of a change in legislation, availability of components or newly acquired experiences. The latest and only valid version of this Technical Data Sheet will be sent to you upon simple request or can be found on our website: [www.crcind.com](http://www.crcind.com) We recommend that you register on our website for this product, thus enabling you to automatically receive any future updates.



# Technical Data Sheet

---

## MAGIC OIL

---

**Version**

CRC\_RED-MAGIC\_OIL-20181115

**Date**

15/11/2018