



SAFETY DATA SHEET

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation of the mixture	Rost Flash
Registration number	-
Synonyms	None.
Product code	BDS000206AE
Issue date	10-March-2021
Version number	01

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Not available.
Uses advised against	None known.

1.3. Details of the supplier of the safety data sheet

Company name	CRC Industries Europe bv
Address	Touwslagerstraat 1 9240 Zele Belgium
Telephone	+32(0)52/45.60.11
Fax	+32(0)52/45.00.34
E-mail	hse@crcind.com
Website	www.crcind.com

1.4. Emergency telephone number

Tel.: +32(0)52/45.60.11 (office hours)

General in EU	112 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Austria National Poisons Information Centre	+431 406 4343 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Belgium National Poisons Control Center	070 245 245 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Bulgaria National Toxicological Information Centre	+359 2 9154233 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Czech Republic National Poisons Information Centre	+420 224 919 293, or +420 224 915 402 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)
Denmark National Poisons Control Center	+45 82 12 12 12 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Estonia National Poisons Information Centre	16662 or abroad: (+372) 626 9390 (Monday 9:00AM to Saturday 9:00AM (closed on Sundays and on national holidays). SDS/Product information may not be available for the Emergency Service.)
Finland National Poison Information Center	(09) 471 977 (direct) or (09) 4711 (exchange) (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
France National Poisons Control Center	ORFILA number (INRS): + 33 (0) 1 45 42 59 59 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Hungary National Emergency Phone Number	36 80 20 11 99 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Lithuania Neatidėliotina informacija apsinuodijus	+370 5 236 20 52 or +37068753378 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)
Malta Accident and Emergency Department	2545 4030 (Hours of operation not provided. SDS/Product information may not be available for the Emergency Service.)

Netherlands National Poisons Information Center (NVIC)	030-274 88 88 (Only for the purpose of informing medical personnel in cases of acute intoxications)
Norway Norwegian Poison Information Center	22 59 13 00 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Romania Biroul RSI si Informare Toxicologica	021.318.36.06 (Available 8:00AM-3:00PM. SDS/Product information may not be available for the Emergency Service.)
Slovakia National Toxicological Information Centre	+421 2 5477 4166 (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)
Sweden National Poison Information Center	112 - and ask for Poison Information (Available 24 hours a day. SDS/Product information may not be available for the Emergency Service.)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Physical hazards		
Aerosols	Category 1	H222 - Extremely flammable aerosol. H229 - Pressurized container: May burst if heated.
Health hazards		
Skin corrosion/irritation	Category 2	H315 - Causes skin irritation.
Environmental hazards		
Hazardous to the aquatic environment, long-term aquatic hazard	Category 3	H412 - Harmful to aquatic life with long lasting effects.

Hazard summary	Aerosol CONTENTS UNDER PRESSURE. Pressurised container may explode when exposed to heat or flame. Causes skin irritation. Dangerous for the environment if discharged into watercourses. Occupational exposure to the substance or mixture may cause adverse health effects.
-----------------------	--

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Hazard pictograms



Signal word Danger

Hazard statements

H222	Extremely flammable aerosol.
H229	Pressurized container: May burst if heated.
H315	Causes skin irritation.
H412	Harmful to aquatic life with long lasting effects.

Precautionary statements

Prevention

P102	Keep out of reach of children.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211	Do not spray on an open flame or other ignition source.
P251	Do not pierce or burn, even after use.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.

Response

Storage

P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
-------------	--

Disposal

P501	Dispose of contents/container in accordance with local/regional/national/international regulations.
------	---

Supplemental label information None.

2.3. Other hazards

This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	Index No.	Notes
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane	0 - 25	EC921-024-6	01-2119475514-35	-	
Classification: Flam. Liq. 2;H225, Skin Irrit. 2;H315, STOT SE 3;H336, Asp. Tox. 1;H304, Aquatic Chronic 2;H411					
Hydrocarbons, C13-15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	5 - 10	EC920-107-4	01-2119453414-43	-	
Classification: Asp. Tox. 1;H304					
Dipropylene glycol monomethyl ether	0 - 2,5	34590-94-8 252-104-2	01-2119450011-60	-	#
Classification: -					

List of abbreviations and symbols that may be used above

#: This substance has been assigned Community workplace exposure limit(s).

M: M-factor

PBT: persistent, bioaccumulative and toxic substance.

vPvB: very persistent and very bioaccumulative substance.

All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume.

Composition comments

The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves.

4.1. Description of first aid measures

Inhalation

Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact

Remove contaminated clothing. Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Wash contaminated clothing before reuse.

Eye contact

Rinse with water. Get medical attention if irritation develops and persists.

Ingestion

In the unlikely event of swallowing contact a physician or poison control centre. Rinse mouth. Do not induce vomiting.

4.2. Most important symptoms and effects, both acute and delayed

Skin irritation. May cause redness and pain.

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards

Extremely flammable aerosol.

5.1. Extinguishing media

Suitable extinguishing media

Foam. Carbon dioxide (CO₂). Dry powder.

Unsuitable extinguishing media

Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

Contents under pressure. Pressurised container may explode when exposed to heat or flame. During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters

Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Special fire fighting procedures

Move containers from fire area if you can do so without risk. Containers should be cooled with water to prevent vapour pressure build up. For massive fire in cargo area, use unmanned hose holder or monitor nozzles, if possible. If not, withdraw and let fire burn out.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials. Use water spray to cool unopened containers. In the event of fire and/or explosion do not breathe fumes.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel Wear appropriate personal protective equipment.

For emergency responders Keep unnecessary personnel away. Use personal protection recommended in Section 8 of the SDS.

6.2. Environmental precautions Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up Stop leak if you can do so without risk. Move the cylinder to a safe and open area if the leak is irreparable. Isolate area until gas has dispersed. Eliminate all ignition sources (no smoking, flares, sparks, or flames in immediate area). Keep combustibles (wood, paper, oil etc) away from spilled material. The product is immiscible with water and will spread on the water surface. Prevent product from entering drains. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

6.4. Reference to other sections For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling Pressurised container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material Do not smoke while using or until sprayed surface is thoroughly dry. Do not cut, weld, solder, drill, grind, or expose containers to heat, flame, sparks, or other sources of ignition. All equipment used when handling the product must be grounded. Do not re-use empty containers. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Use only in well-ventilated areas. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

7.2. Conditions for safe storage, including any incompatibilities Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C. Do not puncture, incinerate or crush. Do not handle or store near an open flame, heat or other sources of ignition. This material can accumulate static charge which may cause spark and become an ignition source. Store away from incompatible materials (see Section 10 of the SDS). Storage class (TRGS 510): 2B (Aerosol dispensers and lighters)

7.3. Specific end use(s) Not available.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

Austria

Components

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane

Type

TWA (MAK)

Value

200 ppm

Austria. MAK List, OEL Ordinance (GwV), BGBl. II, no. 184/2001

Components

Dipropylene glycol monomethyl ether (CAS 34590-94-8)

Type

Ceiling

614 mg/m³

100 ppm

MAK

307 mg/m³

50 ppm

Belgium

Components

Hydrocarbons, C13-15, n-alkanes, isoalkanes, cyclics, < 2% aromatics
mineral oil (IP 346 DMSO extract < 3%)

Type

TWA

200 mg/m³

STEL

10 mg/m³

TWA

5 mg/m³

Belgium. Exposure Limit Values

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	308 mg/m ³
		50 ppm

Bulgaria. OELs. Regulation No 13 on protection of workers against risks of exposure to chemical agents at work

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	308 mg/m ³
		50 ppm

Croatia. Dangerous Substance Exposure Limit Values in the Workplace (ELVs), Annexes 1 and 2, Narodne Novine, 13/09

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	MAC	308 mg/m ³
		50 ppm

Czech Republic. OELs. Government Decree 361

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	Ceiling	550 mg/m ³
	TWA	270 mg/m ³

Denmark

Components	Type	Value
Hydrocarbons, C13-15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	TWA (MAC)	180 mg/m ³
mineral oil (IP 346 DMSO extract < 3%)	TWA	1 mg/m ³

Denmark. Exposure Limit Values

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TLV	309 mg/m ³
		50 ppm

Estonia. OELs. Occupational Exposure Limits of Hazardous Substances (Regulation No. 105/2001, Annex), as amended

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	308 mg/m ³
		50 ppm

Finland

Components	Type	Value
Hydrocarbons, C13-15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	TWA	500 mg/m ³
mineral oil (IP 346 DMSO extract < 3%)	TWA	5 mg/m ³

Finland. Workplace Exposure Limits

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	310 mg/m ³
		50 ppm

France Components	Type	Value
Hydrocarbons, C6-C7, n-alkanes,isoalkanes,cyclic s,< 5% n-hexane	STEL	1500 mg/m3
	TWA	1000 mg/m3
mineral oil (IP 346 DMSO extract < 3%)	STEL	10 mg/m3
	TWA	5 mg/m3

France. Threshold Limit Values (VLEP) for Occupational Exposure to Chemicals in France, INRS ED 984

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	VME	308 mg/m3
Regulatory status:	Regulatory binding (VRC)	50 ppm
Regulatory status:	Regulatory binding (VRC)	

Germany. DFG MAK List (advisory OELs). Commission for the Investigation of Health Hazards of Chemical Compounds in the Work Area (DFG)

Components	Type	Value	Form
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	310 mg/m3	Vapour.
		50 ppm	Vapour.

Germany - TRGS 900

Components	Type	Value
Hydrocarbons, C13-15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	TWA	300 mg/m3
Hydrocarbons, C6-C7, n-alkanes,isoalkanes,cyclic s,< 5% n-hexane	TWA	700 mg/m3

Germany. TRGS 900, Limit Values in the Ambient Air at the Workplace

Components	Type	Value	Form
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	AGW	310 mg/m3	Vapour and aerosol.
		50 ppm	Vapour and aerosol.

Greece. OELs (Decree No. 90/1999, as amended)

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	STEL	900 mg/m3
		150 ppm
	TWA	600 mg/m3 100 ppm

Hungary. OELs. Joint Decree on Chemical Safety of Workplaces

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	308 mg/m3

Iceland. OELs. Regulation 154/1999 on occupational exposure limits

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	300 mg/m3
		50 ppm

Ireland. Occupational Exposure Limits

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	308 mg/m ³
		50 ppm

Italy

Components	Type	Value
mineral oil (IP 346 DMSO extract < 3%)	TWA	5 mg/m ³

Italy. Occupational Exposure Limits

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	308 mg/m ³
		50 ppm

Latvia. OELs. Occupational exposure limit values of chemical substances in work environment

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	308 mg/m ³
		50 ppm

Lithuania. OELs. Limit Values for Chemical Substances, General Requirements

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	STEL	450 mg/m ³
		75 ppm
	TWA	308 mg/m ³
		50 ppm

Luxembourg. Binding Occupational exposure limit values (Annex I), Memorial A

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	308 mg/m ³
		50 ppm

Netherlands

Components	Type	Value
mineral oil (IP 346 DMSO extract < 3%)	TWA (MAC)	5 mg/m ³

Netherlands. OELs (binding)

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	300 mg/m ³

Norway

Components	Type	Value
mineral oil (IP 346 DMSO extract < 3%)	TWA	1 mg/m ³

Norway. Administrative Norms for Contaminants in the Workplace

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TLV	300 mg/m ³
		50 ppm

Poland. Ordinance of the Minister of Labour and Social Policy on 6 June 2014 on the maximum permissible concentrations and intensities of harmful health factors in the work environment, Journal of Laws 2014, item 817

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	STEL	480 mg/m ³
	TWA	240 mg/m ³

Portugal

Components	Type	Value
mineral oil (IP 346 DMSO extract < 3%)	TWA	5 mg/m ³

Portugal. OELs. Decree-Law n. 290/2001 (Journal of the Republic - 1 Series A, n.266)

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	308 mg/m ³
		50 ppm

Portugal. VLEs. Norm on occupational exposure to chemical agents (NP 1796)

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	STEL	150 ppm
	TWA	100 ppm

Romania. OELs. Protection of workers from exposure to chemical agents at the workplace

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	308 mg/m ³
		50 ppm

Slovakia

Components	Type	Value
mineral oil (IP 346 DMSO extract < 3%)	TWA	5 mg/m ³

Slovakia. OELs. Regulation No. 300/2007 concerning protection of health in work with chemical agents

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	308 mg/m ³
		50 ppm

Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	308 mg/m ³
		50 ppm

Spain

Components	Type	Value
Hydrocarbons, C13-15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	TWA (VLA-ED)	200 mg/m ³
mineral oil (IP 346 DMSO extract < 3%)	TWA (VLA-ED)	5 mg/m ³

Spain. Occupational Exposure Limits

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	308 mg/m ³

Spain. Occupational Exposure Limits

Components	Type	Value
		50 ppm

Sweden

Components	Type	Value
Hydrocarbons, C13-15, n-alkanes, isoalkanes, cyclics, < 2% aromatics	TWA	300 mg/m3
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane	STEL (STV)	300 ppm
mineral oil (IP 346 DMSO extract < 3%)	TWA	200 ppm
	STEL (STV)	3 mg/m3
	TWA	1 mg/m3

Sweden. OELs. Work Environment Authority (AV), Occupational Exposure Limit Values (AFS 2015:7)

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	STEL	450 mg/m3
	TWA	75 ppm
		300 mg/m3
		50 ppm

Switzerland Components

Components	Type	Value
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane	TWA	500 ppm

Switzerland. SUVA Grenzwerte am Arbeitsplatz

Components	Type	Value	Form
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	STEL	300 mg/m3	Vapour and aerosol.
	TWA	50 ppm	Vapour and aerosol.
		300 mg/m3	Vapour and aerosol.
		50 ppm	Vapour and aerosol.

UK. EH40 Workplace Exposure Limits (WELs)

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	308 mg/m3
		50 ppm

EU. Indicative Exposure Limit Values in Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU

Components	Type	Value
Dipropylene glycol monomethyl ether (CAS 34590-94-8)	TWA	308 mg/m3
		50 ppm

Biological limit values No biological exposure limits noted for the ingredient(s).**Recommended monitoring procedures** Follow standard monitoring procedures.**Derived no effect levels (DNELs)****General Population**

Components	Value	Assessment factor	Notes	
Dipropylene glycol monomethyl ether (CAS 34590-94-8)				
	Long-term, Systemic, Dermal	121 mg/kg bw/day	16,8	Repeated dose toxicity
	Long-term, Systemic, Inhalation	37,2 mg/m3		Repeated dose toxicity

Long-term, Systemic, Oral	0,33 mg/kg bw/day	600	Repeated dose toxicity
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane (CAS EC921-024-6)			
Long-term, Systemic, Dermal	699 mg/kg bw/day		
Long-term, Systemic, Inhalation	608 mg/m ³		
Long-term, Systemic, Oral	699 mg/kg bw/day		

Workers

Components	Value	Assessment factor	Notes
Dipropylene glycol monomethyl ether (CAS 34590-94-8)			
Long-term, Systemic, Dermal	283 mg/kg bw/day	10,08	Repeated dose toxicity
Long-term, Systemic, Inhalation	308 mg/m ³		Repeated dose toxicity
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane (CAS EC921-024-6)			
Long-term, Systemic, Dermal	773 mg/kg bw/day		
Long-term, Systemic, Inhalation	2035 mg/m ³		

Predicted no effect concentrations (PNECs)

Components	Value	Assessment factor	Notes
Dipropylene glycol monomethyl ether (CAS 34590-94-8)			
Freshwater	19,2 mg/l	100	
Intermittent releases	192 mg/l	10	
Marine water	1,92 mg/l	1000	
Sediment (freshwater)	70,2 mg/kg		
Soil	2,74 mg/kg		

Exposure guidelines

EU Exposure Limit Values: Skin designation

Dipropylene glycol monomethyl ether (CAS 34590-94-8) Can be absorbed through the skin.

Slovenia. OELs. Regulations concerning protection of workers against risks due to exposure to chemicals while working (Official Gazette of the Republic of Slovenia)

Dipropylene glycol monomethyl ether (CAS 34590-94-8) Can be absorbed through the skin.

8.2. Exposure controls

Appropriate engineering controls

Good general ventilation should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level.

Individual protection measures, such as personal protective equipment

General information

Use personal protective equipment as required. Personal protection equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.

Eye/face protection

Use eye protection conforming to EN 166.

Skin protection

- Hand protection

When handling the product wear chemical-resistant gloves (standard EN 374). The breakthrough time of the glove should be longer than the total duration of product use. If work lasts longer than the breakthrough time, gloves should be changed part-way through. Full contact: Glove material: nitrile. Use gloves with breakthrough time of 480 minutes. Minimum glove thickness 0.38 mm.

- Other

Wear appropriate chemical resistant clothing.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. Chemical respirator with organic vapour cartridge. (Filter type A)

Thermal hazards

Wear appropriate thermal protective clothing, when necessary.

Hygiene measures

Handle in accordance with good industrial hygiene and safety practices. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. When using do not smoke.

Environmental exposure controls

Inform appropriate managerial or supervisory personnel of all environmental releases. Contain spills and prevent releases and observe national regulations on emissions. Avoid release to the aquatic environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Form	Aerosol
Colour	Amber.
Odour	Characteristic odor.
Melting point/freezing point	-182 °C (-295,6 °F) estimated

Boiling point or initial boiling point and boiling range	65 - 270 °C (149 - 518 °F)
Flammability (solid, gas)	Not available.
Upper/lower flammability or explosive limits	
Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Flash point	-45,0 °C (-49,0 °F) Closed cup
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
pH	Not applicable.
Solubility(ies)	
Solubility (water)	Insoluble in water
Partition coefficient (n-octanol/water)	Not available.
Vapour pressure	Not available.
Vapour density	Not available.
Relative density	0,74 g/cm ³
Relative density temperature	20 °C (68 °F)
Particle characteristics	Not available.

9.2 Other safety characteristics

Chemical family	Lubricant
Evaporation rate	Not available.
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.
VOC	563 g/l

SECTION 10: Stability and reactivity

10.1. Reactivity	The product is stable and non-reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Material is stable under normal conditions.
10.3. Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
10.4. Conditions to avoid	Avoid high temperatures.
10.5. Incompatible materials	Strong oxidising agents.
10.6. Hazardous decomposition products	Carbon oxides.

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation	Prolonged inhalation may be harmful.
Skin contact	Causes skin irritation.
Eye contact	Direct contact with eyes may cause temporary irritation.
Ingestion	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.

Symptoms Skin irritation. May cause redness and pain.

11.1. Information on toxicological effects

Acute toxicity Based on available data, the classification criteria are not met.

Components	Species	Test Results
Dipropylene glycol monomethyl ether (CAS 34590-94-8)		
Acute		
Dermal		
LD50	Rabbit	9510 mg/kg

Components	Species	Test Results
Oral LD50	Rat	5000 mg/kg
Hydrocarbons, C13-15, n-alkanes, isoalkanes, cyclics, < 2% aromatics		
Acute		
Dermal LD50	Rabbit	5000 mg/kg
Inhalation		
<i>Vapour</i>		
LC50	Rat	5000 mg/kg, 4 h
Oral LD50	Rat	5000 mg/kg
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane		
Acute		
Dermal		
<i>Liquid</i>		
LD50	Rat	2920 mg/kg bw/day, 24 h
Inhalation		
<i>Vapour</i>		
LC50	Rat	25200 mg/m ³ , 4 h
Oral		
<i>Liquid</i>		
LD50	Rat	5840 mg/kg bw/day
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Direct contact with eyes may cause temporary irritation.	
Respiratory sensitisation	Based on available data, the classification criteria are not met.	
Skin sensitisation	Based on available data, the classification criteria are not met.	
Germ cell mutagenicity	Based on available data, the classification criteria are not met.	
Carcinogenicity	Based on available data, the classification criteria are not met.	
Hungary. 26/2000 EüM Ordinance on protection against and preventing risk relating to exposure to carcinogens at work (as amended)		
Not listed.		
Reproductive toxicity	Based on available data, the classification criteria are not met.	
Specific target organ toxicity - single exposure	Based on available data, the classification criteria are not met.	
Specific target organ toxicity - repeated exposure	Based on available data, the classification criteria are not met.	
Aspiration hazard	Not likely, due to the form of the product.	
Mixture versus substance information	Not available.	
11.2. Information on other hazards		
Endocrine disrupting properties	The product does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.	
Other information	Not available.	

SECTION 12: Ecological information

12.1. Toxicity Harmful to aquatic life with long lasting effects.

Components	Species	Test Results
Dipropylene glycol monomethyl ether (CAS 34590-94-8)		
Aquatic		
<i>Acute</i>		
Algae	EC50	Algae 969 mg/l, 96 h
Crustacea	EC50	Daphnia 1919 mg/l, 48 h
Fish	LC50	Fish 10000 mg/l, 96 h

Components	Species		Test Results
<i>Chronic</i>			
Crustacea	NOEC	Daphnia	0,5 mg/l, 22 d
Hydrocarbons, C13-15, n-alkanes, isoalkanes, cyclics, < 2% aromatics			
<i>Acute</i>			
Other	IC50	Pseudokirchnerella subcapitata	1000 mg/l, 72 h
	NOEL	Pseudokirchnerella subcapitata	1000 mg/l, 72 h
Aquatic			
<i>Acute</i>			
Fish	IC50	Oncorhynchus mykiss	1000 mg/l, 96 h
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, < 5% n-hexane			
Aquatic			
<i>Acute</i>			
Algae	EC50	Algae	30 - 100 mg/l, 72 h
Crustacea	EC50	Daphnia	3 mg/l, 48 h
Fish	LC50	Fish	11,4 mg/l, 96 h
12.2. Persistence and degradability	No data is available on the degradability of any ingredients in the mixture.		
12.3. Bioaccumulative potential	No data available.		
Partition coefficient n-octanol/water (log Kow)			
Dipropylene glycol monomethyl ether			0,004
Bioconcentration factor (BCF)	Not available.		
12.4. Mobility in soil	No data available.		
12.5. Results of PBT and vPvB assessment	This mixture does not contain substances assessed to be vPvB / PBT according to Regulation (EC) No 1907/2006, Annex XIII.		
12.6. Endocrine disrupting properties	None known		
12.7. Other adverse effects	The product contains volatile organic compounds which have a photochemical ozone creation potential. GWP: 2		

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Since emptied containers may retain product residue, follow label warnings even after container is emptied. Empty containers should be taken to an approved waste handling site for recycling or disposal. Do not re-use empty containers.
EU waste code	The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Disposal methods/information	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Contents under pressure. Do not puncture, incinerate or crush. Do not allow this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents/container in accordance with local/regional/national/international regulations.
Special precautions	Dispose in accordance with all applicable regulations.

SECTION 14: Transport information

ADR

14.1. UN number	UN1950
14.2. UN proper shipping name	AEROSOLS
14.3. Transport hazard class(es)	
Class	2.1
Subsidiary risk	-
Hazard No. (ADR)	Not available.
Tunnel restriction code	(D)
ADR/RID - Classification code:	5F

- 14.4. Packing group Not applicable
 14.5. Environmental hazards No
 14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IATA

- 14.1. UN number UN1950
 14.2. UN proper shipping name AEROSOLS
 14.3. Transport hazard class(es)
 Class 2.1
 Subsidiary risk -
 14.4. Packing group Not applicable
 14.5. Environmental hazards No
 14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

- 14.1. UN number UN1950
 14.2. UN proper shipping name AEROSOLS
 14.3. Transport hazard class(es)
 Class 2.1
 Subsidiary risk -
 14.4. Packing group Not applicable
 14.5. Environmental hazards
 Marine pollutant No
 EmS F-D, S-U
 14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

- 14.7. Maritime transport in bulk according to IMO instruments Not applicable.

ADR; IATA; IMDG



SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

- Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended
 Not listed.
 Regulation (EU) 2019/1021 On persistent organic pollutants (recast), as amended
 Not listed.
 Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended
 Not listed.
 Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended
 Not listed.
 Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended
 Not listed.
 Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended
 Not listed.
 Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended
 Not listed.
 Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA
 Not listed.

Authorisations

Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorization, as amended

Not listed.

Restrictions on use

Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended

Not listed.

Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.

Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Not listed.

Other regulations

The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended. This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006, as amended.

National regulations

Follow national regulation for work with chemical agents in accordance with Directive 98/24/EC, as amended.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

ADN: European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

ADR: European Agreement Concerning the International Carriage of Dangerous Goods by Road.

AGW: Occupational threshold limit value (Arbeitsplatzgrenzwert – Germany).

ATE: Acute Toxicity Estimate according to REGULATION (EC) No 1272/2008 (CLP).

CAS: Chemical Abstract Service.

Ceiling: Short Term Exposure Limit Ceiling value.

CEN: European Committee for Standardization.

CLP: Classification, Labeling and Packaging REGULATION (EC) No 1272/2008 on classification, labeling and packaging of substances and mixtures.

GWP: Global Warming Potential.

IATA: International Air Transport Association.

IBC Code: International Code for the Construction and Equipment of Ships Carrying Dangerous Chemicals in Bulk.

IMDG: International Maritime Dangerous Goods.

MAC: Maximum Allowed Concentration.

MAK: Threshold limit values Germany (Maximale Arbeitsplatzkonzentration - DFG).

MARPOL: International Convention for the Prevention of Pollution from Ships.

PBT: Persistent, bioaccumulative and toxic.

REACH: Registration, Evaluation and Authorization of Chemicals (REGULATION (EC) No 1907/2006 concerning Registration, Evaluation Authorization and Restriction of Chemicals).

RID: Regulations concerning the international carriage of dangerous goods by rail (Règlement International concernant le transport de marchandises dangereuses par chemin de fer).

RID: Regulations concerning the International Carriage of Dangerous Goods by Rail.

STEL: Short term exposure limit.

TLV: Threshold Limit Value.

TWA: Time Weighted Average.

VLE: Exposure Limit Value.

VME: Exposure Average Value.

VOC: Volatile organic compounds.

vPvB: Very persistent and very bioaccumulative.

STEL: Short-term Exposure Limit.

References

Not available.

Information on evaluation method leading to the classification of mixture

The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available.

Full text of any H-statements not written out in full under Sections 2 to 15

H225 Highly flammable liquid and vapour.

H304 May be fatal if swallowed and enters airways.

H315 Causes skin irritation.

H336 May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

Revision information

None.

Training information

Follow training instructions when handling this material.

Disclaimer

CRC Industries Europe bvba cannot anticipate all conditions under which this information and its product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently available.